



Power	<b>12 W</b>	Voltage	<b>24 V</b>
Luminous flux*	<b>900 lm (90°)</b>	Colour temperature	<b>3000 K</b>
Light colour	<b>WW</b>	Beam angle	<b>25 °</b>
Protection class	<b>IP65</b>		



 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI002016WW
Power	12 W
Nominal current	500 mA
Voltage	24 V
Energy efficiency classe	G
Energy consumption	14 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	0.5
Useful luminous flux*	900 lm (90°)
Luminous flux**	900 lm (360°)
Light efficiency	75 lm/W
Colour temperature	3000 K
Light colour	WW
Beam angle	25 °
RA	70
Light source included	+
Producer of LED diodes	CREE
Uniformity of color SDCM max	6
Dimmable	Yes
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Protection class	IP65
Colour	Gray
Dimension (axbxc)	95x125 mm
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux  
Requires 24V power supply.