





CE

Power	<b>150 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>21000 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>145/75 °</b>
IK	<b>9</b>	Protection class	<b>IP65</b>



 User manual




 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI027018NW_PW
Power	150 W
Nominal current	660 mA
Voltage	230 V
Energy consumption	150 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.9
Useful luminous flux*	21000 lm (360°)
Luminous flux**	20250 lm (360°)
Light efficiency	140 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	145/75 °
RA	70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PC
IK	9
Protection class	IP65
Colour	Gray
Dimension (axbxc)	675x218x124 mm
Mounting hole	60 mm
For use	Outside
Assembly method	On a pole
Application	EXT
Made in	PRC
Other	100-277V ,



\*Applies to the LED source used. \*\*Luminaire luminous flux