



CE

Power	<b>200 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>18000 lm (120°)</b>	Colour temperature	<b>6500 K</b>
Light colour	<b>CW</b>	Beam angle	<b>85 °</b>
IK	<b>10</b>	Protection class	<b>IP65</b>



See more on dedicated page 



 User manual




 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI029057CW_PW
Power	200 W
Nominal current	850 mA
Voltage	230 V
Energy consumption	200 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.99
Useful luminous flux*	18000 lm (120°)
Luminous flux**	18000 lm (360°)
Light efficiency	90 lm/W
Luminous intensity	10500 cd
Colour temperature	6500 K
Light colour	CW
Beam angle	85 °
RA	>80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	Aluminum+PC LENS
IK	10
Protection class	IP65
Colour	Gray
Dimension (axbxc)	410x290x30 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux