
**CE**

| | | | |
|------------------|-----------------------|--------------------|---------------|
| Power | 24 W | Voltage | 230 V |
| Luminous flux* | 2800 lm (360°) | Colour temperature | 4000 K |
| Light colour | Neutral white | Beam angle | 115 ° |
| Protection class | IP54 | | |

 Declaration of Conformity

Technical data:

| | |
|------------------------------|------------------------|
| Product code | SLI031035NW_PW_CZUJNIK |
| Power | 24 W |
| Nominal current | 175 mA |
| Voltage | 230 V |
| Energy consumption | 24 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | + |
| Power factor | 0.6 |
| Useful luminous flux* | 2800 lm (360°) |
| Luminous flux** | 1750 lm (360°) |
| Light efficiency | 117 lm/W |
| Luminous intensity | 1050 cd |
| Colour temperature | 4000 K |
| Light colour | Neutral white |
| Beam angle | 115 ° |
| RA | >80 |
| Light source included | + |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20 +40 ° |
| Lifespan | 17000 h |
| Housing material | TWORZYWO SZTUCZNE |
| Protection class | IP54 |
| Colour | White |
| Dimension (axbxc) | 320x52 mm |
| For use | Inside |
| Assembly method | On the ceiling |
| Application | Inside |
| Made in | PRC |
| Other | MV Sensor , |



*Applies to the LED source used. **Luminaire luminous flux