



CE


---

|                    |               |              |             |
|--------------------|---------------|--------------|-------------|
| Power              | <b>9 W</b>    | Voltage      | <b>24 V</b> |
| Colour temperature | <b>6000 K</b> | Light colour | <b>CW</b>   |
| Beam angle         | <b>120 °</b>  | IK           | <b>06</b>   |
| Protection class   | <b>IP20</b>   |              |             |

---

**Technical data:**

|                              |                   |
|------------------------------|-------------------|
| Product code                 | SLI035002CW_WHITE |
| Power                        | 9 W               |
| Nominal current              | 375 mA            |
| Voltage                      | 24 V              |
| Energy consumption           | 10 kWh/1000h      |
| Frequency                    | DC Hz             |
| Protection class             | III               |
| Luminous flux**              | 520 lm (360°)     |
| Light efficiency             | 57 lm/W           |
| Colour temperature           | 6000 K            |
| Light colour                 | CW                |
| Beam angle                   | 120 °             |
| RA                           | 80                |
| Uniformity of color SDCM max | 5                 |
| Dimmable                     | Yes               |
| Working temperature range    | -20/+40 °         |
| Lifespan                     | 17000 h           |
| Housing material             | Aluminum, PLASTIC |
| IK                           | 06                |
| Protection class             | IP20              |
| Colour                       | White             |
| Dimension (axbxc)            | 150x150x26 mm     |
| For use                      | Inside            |
| Assembly method              | Recessed          |
| Application                  | INT               |
| Made in                      | PRC               |



\*Applies to the LED source used. \*\*Luminaire luminous flux