



CE

|                  |                       |                    |               |
|------------------|-----------------------|--------------------|---------------|
| Power            | <b>26 W</b>           | Voltage            | <b>230 V</b>  |
| Luminous flux*   | <b>4300 lm (360°)</b> | Colour temperature | <b>6000 K</b> |
| Light colour     | <b>CW</b>             | Beam angle         | <b>120 °</b>  |
| Protection class | <b>IP20</b>           |                    |               |



 Declaration of Conformity



 Photometric file

Technical data:

|                              |                           |
|------------------------------|---------------------------|
| Product code                 | SLI035064CW_PW            |
| Power                        | 26 W                      |
| Nominal current              | 115 mA                    |
| Voltage                      | 230 V                     |
| Energy consumption           | 26 kWh/1000h              |
| Frequency                    | 50HZ Hz                   |
| Protection class             | I                         |
| Power supply included        | +                         |
| Power factor                 | 0.9                       |
| Useful luminous flux*        | 4300 lm (360°)            |
| Luminous flux**              | 3900 lm (360°)            |
| Light efficiency             | 165 lm/W                  |
| Colour temperature           | 6000 K                    |
| Light colour                 | CW                        |
| Beam angle                   | 120 °                     |
| RA                           | >80                       |
| Uniformity of color SDCM max | 5                         |
| Dimmable                     | No                        |
| Working temperature range    | -20/+40 °                 |
| Lifespan                     | 50000 h                   |
| Housing material             | Aluminum/Plastic          |
| Protection class             | IP20                      |
| Colour                       | White                     |
| Dimension (axbxc)            | 595x595x32 mm             |
| For use                      | Inside                    |
| Assembly method              | surface mounted, recessed |
| Application                  | INT                       |
| Made in                      | PRC                       |



\*Applies to the LED source used. \*\*Luminaire luminous flux