



Power	<b>40 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>5400 lm (360°)</b>	Colour temperature	<b>3000 K</b>
Light colour	<b>WW</b>	Beam angle	<b>120 °</b>
UGR	<b>&lt;19</b>	Protection class	<b>IP20</b>



 User manual



 Declaration of Conformity



 Photometric file

Technical data:

Product code	SLI035066WW_PW
Power	40 W
Nominal current	185 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	5400 lm (360°)
Luminous flux**	4400 lm (360°)
Light efficiency	135 lm/W
Colour temperature	3000 K
Light colour	WW
Beam angle	120 °
UGR	<19
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/Plastic
Protection class	IP20
Colour	White
Dimension (axbxc)	595x595x32 mm
For use	Inside
Assembly method	surface mounted, recessed
Application	INT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux