



CE

Power	<b>20 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>2300 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>120 °</b>
IK	<b>07</b>	Protection class	<b>IP54</b>



See more on dedicated page 



 User manual



 Declaration of Conformity



 Photometric file



**Technical data:**

Product code	SLI041047NW_PW
Power	20 W
Nominal current	150 mA
Voltage	230 V
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Useful luminous flux*	2300 lm (360°)
Luminous flux**	2100 lm (360°)
Light efficiency	115 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	120 °
RA	>80
Light source included	Yes
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PC
IK	07
Protection class	IP54
Colour	White
Dimension (axbxc)	220x60 mm
For use	Inside/Outside
Assembly method	On the ceiling
Made in	PRC
Other	IP54 ,



\*Applies to the LED source used. \*\*Luminaire luminous flux