

DURE 3 CCT

SLI043007CCT_PW

DURE 3 DOWNLIGHT 12W CCT 230V 110DEG IP54 IK06 FI145X30 WHITE ROUND



Power	12 W	Voltage	230 V
Colour temperature	3000 / 4000 / 6000 K	Colour of light	CCT
Beam angle	110 °	IK	6
Degree of protection (IP)	IP54		

Technical data

Code	SLI043007CCT_PW
Power	12 W
Nominal current	89 mA
Voltage	230 V
Energy consumption	12 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.6
Useful luminous flux*	1500 lm (360°)
Luminous flux	1000 lm (360°)
Lamp efficacy	125 lm/W
Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT
Beam angle	110 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	2 years
Lifespan	17000 h
(On/Off)	15000
Housing material	PS
IK	6
Degree of protection (IP)	IP54
Colour	White
Dimension (AxBxC)	145x30 mm
Mounting hole	125 mm
For use	Inside
Assembly method	Recessed
Application	INT
Certified by the National Institute of Hygiene	Yes
Made in	PRC
Other	Light color change function 3000K / 4000K / 6000K ,


Logistics data

Bulk packaging	60 pcs.
Gross weight (1 pcs.)	0.175 kg


*applies to the LED source used

Related documents



 User manual



 Declaration of Conformity

