

DURE 3 CCT

SLI043011CCT_PW

DURE 3 DOWNLIGHT 18W CCT 230V 110DEG IP54 IK06 170X170X30 WHITE SQUARE

CCT

IP54

IK06



Power	18 W
Colour temperature	3000/4000/6000 K
Beam angle	110 °
Degree of protection (IP)	IP54

Voltage	230 V
Colour of light	CCT
IK	6

Technical data

Logistics data

Code	SLI043011CCT_PW
Power	18 W
Nominal current	130 mA
Voltage	230 V
Energy consumption	18 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.6
Useful luminous flux*	2200 lm (360°)
Luminous flux	1500 lm (360°)
Lamp efficacy	123 lm/W
Colour temperature	3000/4000/6000 K
Colour of light	CCT
Beam angle	110 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Warranty	2 years
Lifespan	17000 h
(On/Off)	15000
Housing material	PS
IK	6
Degree of protection (IP)	IP54
Colour	White
Dimension (AxBxC)	170x170x30 mm
Mounting hole	150x150 mm
For use	Inside
Assembly method	Recessed
Certified by the National Institute of Hygiene	Yes
Made in	PRC
Other	Light color change function 3000K/4000K/6000K ,

Bulk packaging	60 pcs.
Gross weight (1 pcs.)	0.261 kg

*applies to the LED source used

Related documents



 User manual



 Declaration of
Conformity

