

DURE 3 CCT

SLI043022CCT_PW

DURE 3 DOWNLIGHT 9W CCT 230V 110DEG IP54 IK06 F128X31 WHITE ROUND

CCT

IP54

IK06



Power	9 W
Colour temperature	3000/4000/6000 K
Beam angle	110 °
Degree of protection (IP)	IP54

Voltage	230 V
Colour of light	CCT
IK	6

Technical data

Code	SLI043022CCT_PW
Power	9 W
Nominal current	65 mA
Voltage	230 V
Energy consumption	9 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.6
Useful luminous flux*	1000 lm (360°)
Luminous flux	725 lm (360°)
Lamp efficacy	111 lm/W
Colour temperature	3000/4000/6000 K
Colour of light	CCT
Beam angle	110 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Warranty	2 years
Lifespan	17000 h
(On/Off)	15000
Housing material	PS
IK	6
Degree of protection (IP)	IP54
Colour	White
Dimension (AxBxC)	128x31 mm
Mounting hole	105 mm
For use	Inside
Assembly method	Recessed
Certified by the National Institute of Hygiene	Yes
Made in	PRC
Other	Light color change function 3000K/4000K/6000K ,

Logistics data

Bulk packaging	100 pcs.
Gross weight (1 pcs.)	0.13 kg

*applies to the LED source used

Related documents



 User manual



 Declaration of
Conformity

