





Power	<b>17 W</b>	Voltage	<b>48 V</b>
Colour temperature	<b>3000/4000/6000 K</b>	Light colour	<b>CCT</b>
Beam angle	<b>40 °</b>	UGR	<b>&lt;19</b>
Protection class	<b>IP20</b>		




 User manual



 Declaration of Conformity

**Technical data:**

Product code	WLD+40012_SMART
Power	17 W
Nominal current	375 mA
Voltage	48 V
Energy consumption	17 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	1700 lm (360°)
Luminous flux**	850 lm (360°)
Light efficiency	100 lm/W
Luminous intensity	1500 cd
Colour temperature	3000/4000/6000 K
Light colour	CCT
Beam angle	40 °
UGR	<19
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	AL+PC
Protection class	IP20
Colour	Czarny
Dimension (axbxc)	330x23x42 mm
For use	Inside
Assembly method	NA SZYŃĘ
Application	Inside
Made in	PRC
Other	CCT/DIM ,



\*Applies to the LED source used. \*\*Luminaire luminous flux