



| | | | |
|------------------|---------------------|--------------------|---------------|
| Power | 4 W | Voltage | 230 V |
| Luminous flux* | 230 lm (90°) | Colour temperature | 3000 K |
| Light colour | WW | Beam angle | 55 ° |
| Protection class | IP20 | | |

MDR40ECO483055W_MR11

Technical data:

| | |
|------------------------------|---------------------|
| Product code | WOJP06229 |
| Power | 4 W |
| Nominal current | 30 mA |
| Voltage | 230 V |
| Energy consumption | 4 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | + |
| Power factor | 0.5 |
| Useful luminous flux* | 230 lm (90°) |
| Luminous flux** | 300 lm (360°) |
| Light efficiency | 57.5 lm/W |
| Colour temperature | 3000 K |
| Light colour | WW |
| Beam angle | 55 ° |
| RA | 80 |
| Light source included | + |
| Uniformity of color SDCM max | 3 |
| Dimmable | No |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Housing material | Aluminum |
| Protection class | IP20 |
| Colour | White |
| Dimension (axbxc) | 50x175x145 mm |
| For use | Inside |
| Assembly method | On 3-circuit system |
| Application | INT |
| Made in | PL |



*Applies to the LED source used. **Luminaire luminous flux